




Orion D 560F1/NR35VS

Small Poles - Bollard 4 Ways H. 680



Rev. 31/10/2023



Column luminaire, for floor installation, with source light placed on top of fixture with a downwarding emission. This ensure an optimal light distribution on the ground and a better control of glaring effects. Floor fixing bracket with A2 steel clamps. Power supply with driver incorporated with fixed or dimmable output.



PHOTOMETRICAL DATA



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 08

BODY

Pole: Extruded aluminium alloy - Body/Base:
Die-cast aluminium alloy

SCREEN

Sandblasted Glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

SIZES

H 680 x L 160 x W 160

ELECTRICAL SPECIFICATIONS

POWER SUPPLY




220-240Vac 50/60Hz

DRIVER Built-in	SOURCE FLUX 2020 lm	CCT LED 4000K
DRIVER CURRENT 350mA	FIXTURE SOURCE 1200lm	CRI >80
DIMMER SYSTEM DALI available on request	APPARENT EFFICIENCY 59 %	STEP MACADAM 3
SPECIFIC WIRING Inclusa/Included	INSULATION CLASS I	LIFE TIME TM-21 L80B10 50000h
POWER MODULE LED 12W	OVERVOLTAGE PROTECTION 2kV-4kV	PHOTOBIOLOGICAL RISK RG1
ABSORBED POWER 14W	OPERATING TA 50 °	BEAM OPENING Downward/Diffuse >80
SOURCE LED	ENERGETIC CLASS A	

COLORS

							
00 PURE WHITE RAL 9016	01 BLACK RAL 9005	10 WHITE RAL 9010	24 BRONZE	25 RUST	30 ANTHRACIT E	35 SLATE GREY	40 GREY RAL 9006

ACCESSORIES

	MOR683P/2V L82xØ28	Connector IP68 2Way/3Poles. Maximum section 3x2.5mm²
	E.TRA.580 L37xW30xH30 L37xW30xH30	Ultra compact type 2+3 hard wired surge protector. CLI - IP67. Disconnection signaling by indicator. AC disconnection in case of end of life.
	KIT.001	Ground anchoring system with anchor bolts and centring plate